





Safety Barriers

Safety barriers

	Type	V _N (V)	R _{max} without replaceable fuse (Ω)	R _{max} with replaceable fuse	U _o (V)	I _o (mA)	LED	Order No.
	SB-0019	12/12	16+1.2V/ 191	23+1.2V / 197	15.8/15.8	0/88	-	GHG 111 0000 W 0019
	SB-2787	24/24	21+1.2V / 254	41+1.2V / 274	28/28	0/120	X	GHG 111 0000 W 2787
	SB-2427	24/24	21+1.2V / 278	41+1.2V / 298	26.3/26.3	0/102	X	GHG 111 0000 W 2427
	SB-1787	24/24	31+1.2V / 326	51+1.2V / 346	28/28	0/93	X	GHG 111 0000 W 1787
	Type	V _N (V)	R _{max} without replaceable fuse (Ω)	R _{max} with replaceable fuse	U _o (V)	I _o (mA)	LED	Order No.
	SB-1502	12	21 + 1.2 V	41 + 1.2 V	16.8	0	-	GHG 111 0000 W 1502
	Type	V _N (V)	R _{max} without replaceable fuse (Ω)	R _{max} with replaceable fuse	U _o (V)	I _o (mA)	LED	Order No.
	SB-0786	24/24	31+1.2 V/31+1.2V	51+1.2V/51+1.2V	28/28	0/0	-	GHG 111 0000 W 0786
	Type	V _N (V)	R _{max} without replaceable fuse (Ω)	R _{max} with replaceable fuse	U _o (V)	I _o (mA)	LED	Order No.
	SB-0026	1	35	39	6.3	225	-	GHG 111 0000 W 0026
	SB-2710	6	85	105	10	200	-	GHG 111 0000 W 2710
	SB-1602	12	54	60	16.8	390	-	GHG 111 0000 W 1602
	SB-0024	12	166	176	16.8	118	-	GHG 111 0000 W 0024
	SB-0028	15	96	105	20.1	258	-	GHG 111 0000 W 0028
	SB-0029	15	220	229	20.1	106	-	GHG 111 0000 W 0029
	SB-1203	18	464	476	27	66	-	GHG 111 0000 W 1203

PEPPERL+FUCHS
68301 Mannheim Germany / www.pepperl-fuchs.com

SB 2787 GHG 111 0000 W 2787
Serial No. 0030809444
Part No. 540565

II (1/2) G D [EEEx ia/ib] IIC TUV 99 ATEX 1449 X



CE 0102

PROCESS CONT. EQ.
DC DOUBLE BARRIER,
1 RETURN

U_o: 28 / 28 V; I_o: 300 / 120 mA; P_o: 115 / 840 mW;
C_o: 0.070 µF; L_o: 0.35 / 1 mH
U_N: 24 / 24 V -20°C ≤ T_a ≤ 60°C Um=250V

Made in Germany

Note

Barriers will be supplied without sockets.
Please order socket separately (Page 7/2).
All barriers can be ordered using the type
number or the full order no. GHG....